



Refrigerated container for the transport of temperature-controlled products

- Brand: MELFORM
- Country of origin: ITALY
- Customs code: 84181080
- Compatible with food contact
- Color: melange grey/blue
- Dual power supply: 12Vdc and 230Vac
- Technology: rotomoulding
- Warranty: 24 months
- Fully recyclable at the end of its operational life.








MANUFACTURING MATERIALS

Polyethylene	internal and external walls of the container and door; suitable for food contact	Polyurethane	insulating material between the walls of the container and the door; CFC and HCFC free
Silicone rubber	gasket	Stainless steel	handle and closing hooks, gripping handles
Aluminium	Crankcase control panel		









Model	Code product	Code EAN	Ext. dim. (mm)	Int. dim. (mm)	Capacity (liters)	Weight (kg)
integrated fridge	K32AFISDYM0	8022949177744	420x753xh493	268x372xh322	32	30
	K32AFISCYM0	8022949177690				
	K32AFISBYM0	8022949177461				
	K32AFISAYM0	8022949177218				
	K32AFISDZM0	8022949178017				
	K32AFISCZM0	8022949177423				
	K32AFISBZM0	8022949177393				
	K32AFISAZM0	8022949177713				



FEATURES COOLING UNIT

	Static cooling unit version equipped with "roll-bond" type static evaporator		Hermetic compressor with electronic control unit for regulation and control equipped with surge protection
	Guaranteed refrigeration unit performance for ambient T-use: +10°C to +30°C Container (isothermal case) guaranteed for use: -30°C to +100°C		Cables for 230Vac 50-60Hz power supply (<u>standard equipment</u>)
	Cables for 12Vdc power supply with Anderson terminals (<u>standard equipment</u>)		Cables for 12Vdc power supply with Anderson terminal on the KOALA side and cigarette lighter plug (<u>present depending on the model</u>)
	Cables for 12Vdc power supply with Anderson terminal on the KOALA side and fork terminal for connection to the vehicle battery (<u>present depending on the model</u>)		
<p>Degree of accuracy: +/-0.5 °C Refrigerant gas: R134a (versions 0°C +10/+40°C; -18°C +10/+40°C; -25°C +10/+40°C); R452a (version -30°C +10/+40°C)</p>			

PRODUCT FEATURES

	Door sealing gasket fixed with stainless steel dots		Evaporator protection grid made of plasticized wire
	Practical and resistant locking system		Stainless steel grip handles integrated into the body
	Adjustable relief valve		Temperature regulation and control with programmable digital thermostat
	USB datalogger available (on request) to record temperature data during transport		RFID systems for traceability

Model	Product code	12V supply Fork terminal	12V supply Cigarette lighter plug	Absorption nominal	Fuses
Koala 32 AF 0°C to +10°C C	K32AFISDYM0		✓	0.35A at 230Vac 7A at 12Vdc (85 W)	4A for 230Vac 15A for 12Vdc
Koala 32 AF -18°C to +10°C	K32AFISCYM0	✓		0.62A at 230Vac 12A to 12Vdc (150 W)	4A for 230Vac 25A for 12Vdc
Koala 32 AF -25°C to +10°C	K32AFISBYM0	✓		0.62A at 230Vac 12A to 12Vdc (150 W)	4A for 230Vac 25A for 12Vdc
Koala 32 AF -30°C to +10°C	K32AFISAYM0	✓		1A at 230Vac 18A at 12Vdc (220 W)	4A for 230Vac 30A for 12Vdc
Koala 32 AFH 0°C to +40°C	K32AFISDZM0		✓	0.35A at 230Vac 7A at 12Vdc (85 W)	4A for 230Vac 15A for 12Vdc
Koala 32 AFH -18°C to +40°C	K32AFISCZM0	✓		0.62A at 230Vac 12A at 12Vdc (150 W)	4A for 230Vac 25A for 12Vdc
Koala 32 AFH -25°C to +40°C	K32AFISBZM0	✓		0.62A at 230Vac 12A to 12Vdc (150 W)	4A for 230Vac 25A for 12Vdc
Koala 32 AFH -30°C to +40°C	K32AFISAZM0	✓		1A at 230Vac 18A at 12Vdc (220 W)	4A for 230Vac 30A for 12Vdc

ACCESSORIES	Code
Fixing kit modular system	RRI136
Fixing kit on vehicle	RRI144